

CARRABILI DRIVEWAY



Sono gli incassi a terra storici di Civic. Le nuove fonti luminose e la nuova tecnologia produttiva mantengono questa collezione originale e al passo con i tempi. La famiglia è realizzata interamente in acciaio Inox offrendo maggior resistenza e durata nel tempo.

Civic's historic ground recessed range. The new sources and the new production technology, maintains this range up to date. The construction entirely in Stainless steel ensure reliability and quality along the time.



Carrabili



Era
Diana



Perseo
Zeus







ZEUS

Corpo e anello di chiusura in acciaio inox AISI 304. Grado di protezione IP67. Schermo di protezione in vetro trasparente temperato di spessore 12mm con resistenza meccanica IK 10 per passaggio veicolare. Guarnizione in gomma al silicone. Riflettore fisso asimmetrico o orientabile. Equipaggiato con un LED di colore bianco 4000K o 3000K. Potenze da 17W a 24W. Fornito completo di driver integrato nella struttura e di cavo di collegamento H05RN-F 3x1mm².

Structure and closing ring made of AISI 304 stainless steel. IP67 protection degree. Protection shield made of transparent tempered glass with 12mm thickness and IK 10 shock resistance for vehicle passage use. Silicone rubber gasket. Fixed, asymmetric or adjustable reflector. Equipped with one LED in 4000K or 3000K color temperature. Power from 17W up to 24W. Supplied with built-in driver and H05RN-F 3x1mm² connecting cable.



PERSEO

Corpo e anello di chiusura in acciaio inox AISI 304. Grado di protezione IP67. Schermo di protezione in vetro trasparente temperato di spessore 12mm con resistenza meccanica IK 10 per passaggio veicolare. Guarnizione in gomma al silicone. Riflettore fisso asimmetrico o orientabile. Equipaggiato con un LED di colore bianco 4000K o 3000K. Potenza 17W. Fornito completo di driver integrato nella struttura e di cavo di collegamento H05RN-F 3x1mm².

Structure and closing ring made of AISI 304 stainless steel. IP67 protection degree. Protection shield made of transparent tempered glass with 12mm thickness and IK 10 shock resistance for vehicle passage use. Silicone rubber gasket. Fixed, asymmetric or adjustable reflector. Equipped with one LED in 4000K or 3000K color temperature. Power 17W. Supplied with built-in driver and H05RN-F 3x1mm² connecting cable.

| | |
|-----------|---------------------|
| CE | IP67 |
| LED | RG1 |
| CRI 80/90 | Driver on/off incl. |
| L80 B10 | Driveover Carrabile |
| 50000H | Mac Adam 3 |
| | |



Z E U S

D.
OPTIC
38° 1

OPTIC
20° 2

OPTIC
13° 3


X.
CRI80
5

CRI90
6


Y.
4000K
7

3000K
8


FISSO / FIXED



ORIENTABILE / ADJUSTABLE



ASIMMETRICO / ASYMMETRIC



COD. ON/OFF

D.MM

W

LM

DRIVER

FISSO / FIXED

JEZ.5580. D X Y

Ø260

24W/230V LED

3710/3550

built-in/incorporato

ORIENTABILE / ADJUSTABLE

JEZ.5581. D X Y

Ø260

17W/230V LED

2700/2550

built-in/incorporato

ASIMMETRICO / ASYMMETRIC

JEZ.5582. 1 X Y

Ø260

24W/230V LED


3710/3550

built-in/incorporato

ACCESSORI / ACCESSORIES



JEZ.FG
Vetro sabbato
Sanded glass.



JEZ.FR2
Cornice quadrata
Square ring.



AAA.CN3
Connettore IP68, 3vie.
IP68 waterproof connector, 3way.




AAA.CN4
Connettore IP68, 4vie.
IP68 waterproof connector, 4way.




| | |
|------------|---------------------|
| CE | IP67 |
| LED | RG1 |
| CRI 80/90 | Driver on/off incl. |
| L80 B10 | Driveover Carrabile |
| 50000H | Mac Adam 3 |
| ⏚ | |

PERSEO


FISSO / FIXED



ORIENTABILE / ADJUSTABLE



ASIMMETRICO / ASYMMETRIC



D.
OPTIC
38°
1

OPTIC
20°
2

OPTIC
13°
3

X.
CRI80
5

CRI90
6

Y.
4000K
7

3000K
8

COD. ON/OFF

D.MM

W

LM

DRIVER

FISSO / FIXED

JEP.5590. D X Y

Ø230

17W/230V LED

2700/2550

built-in/incorporato

ORIENTABILE / ADJUSTABLE

JEP.5591. D X Y

Ø230

17W/230V LED

2700/2550

built-in/incorporato

ASIMMETRICO / ASYMMETRIC

JEP.5592. D X Y

Ø230

17W/230V LED


2700/2550

built-in/incorporato

ACCESSORI / ACCESSORIES



JEP.FG
Vetro sabbato
Sanded glass.



JEP.FR2
Cornice quadrata
Square ring.



AAA.CN3
Connettore IP68, 3vie.
IP68 waterproof connector, 3way.



AAA.CN4
Connettore IP68, 4vie.
IP68 waterproof connector, 4way.





ERA

Corpo e anello di chiusura in acciaio inox AISI 304. Grado di protezione IP67. Schermo di protezione in vetro trasparente temperato di spessore 10mm con resistenza meccanica IK 10 per passaggio veicolare. Guarnizione in gomma al silicone. Equipaggiato con un LED di colore bianco 4000K o 3000K. Potenza da 13W. Fornito completo di driver integrato nella struttura e di cavo di collegamento H05RN-F 3x1mm².

Structure and closing ring made of AISI 304 stainless steel. IP67 protection degree. Protection shield made of transparent tempered glass with 10mm thickness and IK 10 shock resistance for vehicle passage use. Silicone rubber gasket. Fixed reflector. Equipped with one LED in 4000K or 3000K color temperature. Power 13W. Supplied with built-in driver and H05RN-F 3x1mm² connecting cable.



DIANA



Corpo e anello di chiusura in acciaio inox AISI 304. Grado di protezione IP67. Schermo di protezione in vetro trasparente temperato di spessore 10mm con resistenza meccanica IK 10 per passaggio veicolare. Guarnizione in gomma al silicone. Ottica fissa o orientabile. Equipaggiato con LED di colore bianco da 4000K o 3000K con potenza 9W o con portalampada GU10 o RGB 6W, fornito completo di driver integrato nella struttura e di cavo di collegamento H05RN-F 3x1mm². Disponibile anche nella versione RGB con potenza 6W.

Structure and closing ring made of AISI 304 stainless steel. IP67 protection degree. Protection shield made of transparent tempered glass with 10mm thickness and IK 10 shock resistance for vehicle passage use. Silicone rubber gasket. Fixed or adjustable optic. Equipped with one LED in 4000K or 3000K color temperature power 9W or with GU10 lampholder or 6W RGBc, supplied with built-in driver and H05RN-F 3x1mm² connecting cable. Also available in RGB version power 6W.

| | |
|-----------|---------------------|
| CE | IP67 |
| LED | RG1 |
| CRI 80/90 | Driver on/off incl. |
| L80 B10 | Driveover Carrabile |
| 50000H | Mac Adam 3 |
| ⏚ | |



ERA

D.
OPTIC
45° 1

OPTIC
24° 2

OPTIC
10° 3


X.
CRI80
5

CRI90
6

Y.
4000K
7

3000K
8

FISSO / FIXED



COD. ON/OFF

D.MM

W

LM

DRIVER

FISSO / FIXED

JEL.5540. D X Y

Ø178

13W/230V LED


2100/2000

built-in/incorporato

ACCESSORI / ACCESSORIES



JEL.FG
Vetro sabbato
Sanded glass.



JEL.FR2
Cornice quadrata
Square ring.



AAA.CN3
Connettore IP68, 3vie.
IP68 waterproof connector, 3way.






AAA.CN4
Connettore IP68, 4vie.
IP68 waterproof connector, 4way.



| | |
|------------|---------------------|
| CE | IP67 |
| LED | RG1 |
| CRI 80/90 | Driver on/off incl. |
| L80 B10 | Driveover Carrabile |
| 50000H | Mac Adam 3 |
| | |

DIANA



- D.** OPTIC 36° 1
- OPTIC 24° 2
- OPTIC 12° 3
- X.** CRI80 5
- CRI90 6
- Y.** 4000K 7
- 3000K 8
- 2700K 9

| COD. ON/OFF | D.MM | W | LM | DRIVER | |
|--------------------------|------|---|-------------|----------------------|------------------|
| FISSO / FIXED | | | | | |
| JEO.5502. D X Y | Ø110 | 9W/230V LED | 890/840/770 | built-in/incorporato | |
| JEO.35FGUB | Ø110 | 20W/230V GU10 lamp. esclusa/lamp excluded | | | |
| ORIENTABILE / ADJUSTABLE | | | | | |
| JEO.5503. D X Y | Ø110 | 9W/230V LED | 890/840/770 | built-in/incorporato | |
| JEO.35MGUB | Ø110 | 20W/230V GU10 lamp. esclusa/lamp excluded | | | |
| COD. ON/OFF | D.MM | W | LM | FASCIO / BEAM | DRIVER |
| FISSO / FIXED RGB | | | | | |
| JEO.5502.299 | Ø110 | 6W/24V LED RGB | 420 | 25° | excluded/escluso |

ACCESSORI / ACCESSORIES




JEO.C1
Calottina a 1 finestra.
1 window dome.

JEO.C2
Calottina a 2 finestra.
2 windows dome.



JEO.FG
Vetro sabbaiato
Sanded glass.



JEO.FR2
Cornice quadrata
Square ring.



JEO.MS
Master JEO RGB.

JEO.SL
Slave JEO RGB.



AAA.CN3
Connettore IP68, 3vie.
IP68 waterproof connector, 3way.



AAA.CN4
Connettore IP68, 4vie.
IP68 waterproof connector, 4way.