

MINI RAGGIO SPOT

Mini Raggio Spot arricchisce la famiglia di proiettori per esterni Raggio. Le dimensioni ridotte al minimo e l'ampia gamma di lenti a corredo permettono la massima precisione nell'illuminazione da una sorgente di dimensioni essenziali. Soluzione particolarmente adatta per giardini, cespugli, aiuole e consigliata anche in campo architettonico.

Mini Raggio Spot enriches the outdoor floodlights family Raggio. The minimum dimensions and the wide range of lenses available, allows maximum lighting precision from an essential dimension source. Suggested solution for gardens, bushes, flower beds and recommended to enhance architectural details of walls and facades.



MINI RAGGIO SPOT

Corpo e anello di chiusura in lega primaria di alluminio sottoposti a pre-trattamento di anodizzazione galvanica. Verniciatura a doppio strato a polveri epossipoliestere. Grado di protezione IP65. Schermo di protezione in vetro trasparente temperato. LED tono luce bianco 4000K o 3000K da alimentare a 24V. Viteria in acciaio inox A4. Potenza 3W. Fornito completo di cavo di collegamento H05RN-F 2x0.5mm². Staffa inclusa.

Body and closing ring in aluminum alloy with galvanic anodizing pre-treatment. Double layer Epoxy-polyester double step painting process. IP65 Protection degree. Diffuser made of transparent tempered glass. Equipped with one LED in 4000K or 3000K white colour to be supplied at 24V. Power 3W. Supplied with H05RN-F 2x0.5mm² connecting cable. Bracket included.

CE	IP65
LED	RG1
CRI 90	Mac Adam 3
L80 B10	
50000H	



MINI RAGGIO SPOT

Z. COLOR	antracite / anthracite - 06	
	bianco raggrinzante/rough white - 32	
	grigio chiaro opaco/clear matt grey - 37	
	corten/corten - 39	

D. 15°
1


60°
2

10°x45°
3

CRI90
6

4000K
7

3000K
8



COD. ON/OFF	W	K	LM	DRIVER	FASCIO / BEAM
LAA.5105. D 6 7. Z	3W/24V LED	4000	360	escluso/excluded	15°/60°/10°x45°
LAA.5105. D 6 8. Z	3W/24V LED	3000	339	escluso/excluded	15°/60°/10°x45°

ACCESSORI / ACCESSORIES



LAA.SP01
Picchetto Inox.
Inox Spike.



AAA.CN2
Connettore IP68, 2 vie.
IP68 waterproof connector, 2 way.



LAA.AS01
Asta h.300mm con picchetto.
Rod h.300mm with spike.



AAA.CN3
Connettore IP68, 3 vie.
IP68 waterproof connector, 3 way.



AAA.TRS13
Driver 70W, IP67.
Driver 70W, IP67.



AAA.CN4
Connettore IP68, 4 vie.
IP68 waterproof connector, 4 way.

