



Luminaire		Measur.		Lamp	
Code	F44.3213.057	Code	F44_30W.LDT	Code	
Name	PARETE 30W LED	Name	PARETE 30W LED	Number	0
Line	aaa	Date	13-07-2016	Position	
Efficiency	100.02%	Coordinate system	C-G	Total Flux	3090.00 lm
Maximum value	221.80 cd/klm	Position	C=0.00 G=0.00	Double Symmetrical	

UGR
S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
WorkingPlane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
RoomDimensions	ViewedCrosswise					ViewedEndwise				
x=2H y=2H	19.0	20.2	19.5	20.7	20.2	17.9	19.1	18.4	19.6	20.2
x=2H y=3H	21.1	22.2	21.7	22.8	21.6	19.3	20.4	19.9	21.0	21.6
x=2H y=4H	22.1	23.1	22.7	23.7	22.1	19.8	20.9	20.4	21.5	22.1
x=2H y=6H	23.1	24.1	23.7	24.7	22.5	20.2	21.2	20.8	21.8	22.5
x=2H y=8H	23.6	24.5	24.2	25.1	22.6	20.3	21.3	21.0	21.9	22.6
x=2H y=12H	24.0	24.9	24.7	25.6	22.6	20.4	21.3	21.0	21.9	22.6
x=4H y=2H	19.6	20.6	20.2	21.2	21.1	18.8	19.8	19.4	20.4	21.1
x=4H y=3H	22.0	22.8	22.6	23.5	22.7	20.4	21.3	21.1	22.0	22.7
x=4H y=4H	23.1	23.9	23.8	24.6	23.3	21.1	21.9	21.8	22.6	23.3
x=4H y=6H	24.3	25.0	25.0	25.7	23.8	21.7	22.4	22.4	23.1	23.8
x=4H y=8H	24.9	25.6	25.6	26.3	24.0	21.8	22.5	22.5	23.2	24.0
x=4H y=12H	25.5	26.1	26.2	26.8	24.1	22.0	22.6	22.7	23.3	24.1
x=8H y=4H	23.5	24.1	24.2	24.8	24.0	21.8	22.5	22.5	23.2	24.0
x=8H y=6H	24.9	25.5	25.6	26.2	24.7	22.6	23.2	23.3	23.9	24.7
x=8H y=8H	25.6	26.1	26.4	26.9	25.0	23.0	23.4	23.7	24.2	25.0
x=8H y=12H	26.4	26.8	27.1	27.5	25.2	23.2	23.6	23.9	24.4	25.2
x=12H y=4H	23.5	24.1	24.2	24.8	24.1	22.0	22.6	22.7	23.3	24.1
x=12H y=6H	25.0	25.5	25.7	26.2	25.0	22.9	23.4	23.6	24.1	25.0
x=12H y=8H	25.8	26.2	26.5	27.0	25.4	23.3	23.8	24.1	24.5	25.4