

Luminaire		Measur.		Lamp	
Code	F44.3213.058.02	Code	140015EC	Code	
Name	F44 LED 25W LED ww	Name	F44 LED 12,5W LED ww	Number	0
Line	aaa	Date	28-03-2014	Position	
Efficiency	57.50%	Coordinate system	C-G	Total Flux	1502.00 lm
Maximum value	169.92 cd/klm	Position	C=0.00 G=0.00	Asymmetrical	

UGR
S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
WorkingPlane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
RoomDimensions	ViewedCrosswise					ViewedEndwise				
x=2H y=2H	15.4	16.9	15.7	17.1	17.9	16.0	17.4	16.3	17.6	17.9
x=2H y=3H	17.2	18.5	17.5	18.8	18.9	17.0	18.4	17.3	18.6	18.9
x=2H y=4H	18.0	19.2	18.3	19.5	19.2	17.3	18.6	17.7	18.9	19.2
x=2H y=6H	18.7	19.9	19.1	20.2	19.3	17.5	18.7	17.9	19.0	19.3
x=2H y=8H	19.0	20.2	19.4	20.5	19.3	17.5	18.7	17.9	19.0	19.3
x=2H y=12H	19.4	20.4	19.8	20.8	19.3	17.5	18.6	17.9	18.9	19.3
x=4H y=2H	16.4	17.6	16.7	17.9	18.6	16.8	18.0	17.1	18.3	18.6
x=4H y=3H	18.3	19.4	18.7	19.7	19.9	18.2	19.3	18.6	19.6	19.9
x=4H y=4H	19.2	20.2	19.6	20.6	20.4	18.7	19.7	19.1	20.0	20.4
x=4H y=6H	20.1	21.0	20.5	21.3	20.7	19.0	19.9	19.4	20.2	20.7
x=4H y=8H	20.5	21.3	21.0	21.7	20.7	19.1	19.9	19.5	20.3	20.7
x=4H y=12H	20.9	21.6	21.4	22.1	20.7	19.1	19.8	19.6	20.3	20.7
x=8H y=4H	19.7	20.5	20.2	20.9	20.9	19.3	20.1	19.7	20.5	20.9
x=8H y=6H	20.8	21.5	21.3	21.9	21.5	19.9	20.6	20.4	21.0	21.5
x=8H y=8H	21.4	22.0	21.9	22.4	21.7	20.1	20.8	20.6	21.2	21.7
x=8H y=12H	21.9	22.4	22.4	22.9	21.8	20.3	20.8	20.8	21.3	21.8
x=12H y=4H	19.8	20.5	20.2	20.9	21.0	19.4	20.1	19.8	20.5	21.0
x=12H y=6H	21.0	21.6	21.5	22.0	21.7	20.2	20.8	20.6	21.2	21.7
x=12H y=8H	21.6	22.1	22.1	22.6	22.0	20.5	21.0	21.0	21.5	22.0