



Mini Tebe testa + stelo in policarbonato trasparente  
H=1050mm, 10W, 230V, 2700K, antracite

Mini Tebe head + polycarbonate trasparent pole  
H=1050mm, 10W, 230V, 2700K, anthracite



### Descrizione/Description

IT: Testa in acciaio inox con verniciatura a polvere di poliestere. Steli in policarbonato o acciaio inox verniciato. Schermo in policarbonato opale. Guarnizione in gomma di silicone. Equipaggiato con LED 4000K, 3000K o 2700K. Potenza 10W. Proposto in due soluzioni, a 230V o 24V. Grado di protezione IP65. Rischio fotobiologico RG0. Cavo di collegamento H05RN-F.

ENG: Head made of stainless steel with polyester powder coating. Stems in polycarbonate or stainless steel coated. Opal polycarbonate diffuser. Silicone rubber gasket. Equipped with white LED 4000K, 3000K o 2700K. Power 10W. Available in 230V or 24V. IP65 protection degree. Photobiological risk RG0. Supplied complete with H05RN-F connection cable.

<b>Codice/Code</b>	MTY.7170.259.06
<b>Tonalità/Light tone</b>	2700K
<b>Potenza/Power</b>	10W
<b>Fusso luminoso/Luminous flux</b>	501 lm - 1000 lm
<b>Colore/Color</b>	Grigio antracite
<b>Driver/Driver</b>	Driver On/Off



Accessori/Accessories



AAA.CN2000.00  
Connettore IP68, 2 vie.

AAA.CN2000.00  
IP68 waterproof connector, 2 ways.