



Mini Tebe testa + stelo in policarbonato trasparente
H=1050mm, 10W, 24V, 2700K, antracite

Mini Tebe head + polycarbonate trasparent pole
H=1050mm, 10W, 24V, 2700K, anthracite



Descrizione/Description

IT: Testa in acciaio inox con verniciatura a polvere di poliestere. Steli in policarbonato o acciaio inox verniciato. Schermo in policarbonato opale. Guarnizione in gomma di silicone. Equipaggiato con LED 4000K, 3000K o 2700K. Potenza 10W. Proposto in due soluzioni, a 230V o 24V. Grado di protezione IP65. Rischio fotobiologico RG0. Cavo di collegamento H05RN-F.

ENG: Head made of stainless steel with polyester powder coating. Stems in polycarbonate or stainless steel coated. Opal polycarbonate diffuser. Silicone rubber gasket. Equipped with white LED 4000K, 3000K o 2700K. Power 10W. Available in 230V or 24V. IP65 protection degree. Photobiological risk RG0. Supplied complete with H05RN-F connection cable.

Codice/Code	MTY.7174.259.06
Tonalità/Light tone	2700K
Potenza/Power	10W
Fusso luminoso/Luminous flux	501 lm - 1000 lm
Colore/Color	Grigio antracite
Driver/Driver	Driver On/Off



Accessori/Accessories



AAA.CN2000.00
Connettore IP68, 2 vie.

AAA.CN2000.00
IP68 waterproof connector, 2 ways.



AAA.TRSL08.00
Driver LED tensione costante 24V 30W

AAA.TRSL08.00
Driver LED constant voltage 24V 30W.



AAA.TRSL13.00
Driver LED 24V 70W IP67

AAA.TRSL13.00
Driver LED constant voltage 24V 70W IP67.