




Micro Tebe testa + stelo in policarbonato trasparente H=1050mm, 5W, 230V, 4000K, antracite

Micro Tebe head + polycarbonate trasparent pole H=1050mm, 5W, 230V, 4000K, anthracite



Descrizione/Description



IT: Testa in acciaio inox con verniciatura a polvere di poliestere. Steli in policarbonato o acciaio inox verniciato. Schermo in policarbonato opale. Guarnizione in gomma di silicone. Equipaggiato con LED 4000K, 3000K o 2700K. Potenza 5W. Proposto in due soluzioni, a 230V o 24V. Grado di protezione IP65. Rischio fotobiologico RG0. Cavo di collegamento H05RN-F.

ENG: Head made of stainless steel with polyester powder coating. Stems in polycarbonate or stainless steel coated. Opal polycarbonate diffuser. Silicone rubber gasket. Equipped with white LED 4000K, 3000K or 2700K. Power 5W. Available in 230V or 24V. IP65 protection degree. Photobiological risk RG0. Supplied complete with H05RN-F connection cable.

Codice/Code	MTY.7250.257.06
Tonalità/Light tone	4000K
Potenza/Power	5W
Fusso luminoso/Luminous flux	501 lm - 1000 lm
Colore/Color	Grigio antracite
Driver/Driver	Driver On/Off



Accessori/Accessories



AAA.CN2000.00
Connettore IP68, 2 vie.

AAA.CN2000.00
IP68 waterproof connector, 2 ways.